

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 986 293 A1

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
15.03.2000 Bulletin 2000/11

(51) Int. Cl.<sup>7</sup>: H05K 9/00

(21) Application number: 98307227.3

(22) Date of filing: 08.09.1998

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI


(71) Applicant:  
Lucent Technologies Inc.  
Murray Hill, New Jersey 07974 (US)

(72) Inventors:  
• Falaki, Hamid Reza  
Peatmoor, Swindon, Wiltshire SN5 5A (GB)  
• Sparkes, Stephen  
Farnborough GU1 40HX (GB)  
• Thompson, Brian John  
Reading RG2 8QR (GB)

(74) Representative:  
Johnston, Kenneth Graham et al  
5 Mornington Road  
Woodford Green Essex, IG8 OTU (GB)

## (54) Radio frequency electronic apparatus

(57) Electronic apparatus has modules operating at radio frequencies. The modules comprise components operatively mounted on a common circuit board contained by a conductive case which is subdivided by internal partition walls separating modules one from another. The partition walls extend from a base at an outer wall of the case to an apex adjacent the circuit board. The apex is sealed to the circuit board by a deposited compressible conductive gasket. The thickness of a circuit board is subject to wide tolerance, for example 10% in the case of multilayer circuit board. The gasket allows the screen to be carried right to the board so that electrical contact can be obtained between an earth track on the board and the partition wall of the case.



EP 0 986 293 A1

1

EP 0 986 293 A1

2

## Description

[0001] This invention relates to electronic apparatus operating at radio frequencies.

[0002] When apparatus is operative at radio frequencies it is often necessary to screen it against radio frequency emissions, both as a whole and to screen one module of the apparatus from another. Ineffective screening can lead to feedback and interference problems.

[0003] Against this background, there is provided electronic apparatus having modules operating at radio frequencies, said modules comprising components operatively mounted on a common circuit board contained by a conductive case which is subdivided by internal partition walls separating modules one from another, the partition walls extending from a base at an outer wall of the case to an apex adjacent the circuit board, the apex being sealed to the circuit board by a deposited compressible conductive gasket. The thickness of a circuit board is subject to wide tolerance, for example 10% in the case of multilayer circuit board. The gasket allows the screen to be carried right to the board so that electrical contact can be obtained between a track on the board and the partition wall of the case.

[0004] Preferably, the gasket is deposited on the apex of the partition walls.

[0005] In one embodiment the internal partition walls extend from opposite outer walls of the case towards opposite sides of the circuit board.

[0006] Most preferably the peripheral walls are stepped complementarily in transverse cross section to provide pairs of opposed surfaces at two levels, one pair of the surfaces being in direct contact with each other, the other pair extending to opposed sides of the circuit board and at least one having a compressible conductive gasket deposited thereon. This allows the surfaces in direct contact to operate as a dead stop, preventing the gasket from being over tightened.

[0007] One embodiment of the invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is an exploded pictorial view of a transmit receive unit embodying the invention;

Figure 2a is a section along the line P-P of the assembled unit of Figure 1 in the direction of the arrows;

Figure 2b is a transverse cross section through a peripheral wall of the case of the unit of Figure 1;

Figure 3 is a plan view of a power amplifier embodying the invention; and

Figure 4 is a section on arrows Q-Q of Figure 3.

[0008] Referring to the drawings, a transmit receive unit is constructed on a two sided multilayer circuit board 2 which is contained by an aluminium case constructed in two parts 4,6. The case acts as a RF (radio

frequency) screen. The components of two transmitters and two receivers are mounted on the board 2. Base band data to be transmitted and data received are input and output on multipin connectors 8 and 10. Radio frequency signals received by antennas (not shown) are input via a duplexer on co-axial sockets 12 and 14. Radio frequency signals to be transmitted by the antennas are output from co-axial sockets 16 and 18 to power amplifiers (not shown).

[0009] The components are mounted on both sides of the board and are arranged in a number of sub-modules. Each module is required to be RF screened from the others to prevent feedback and interference problems.

[0010] On the circuit board each module is surrounded by an earth track 70. The components of each module are contained by internal partition walls 72 which are formed integrally with the walls 76 of the casing and which extend from a base 74 at an outer wall 76 of the part 4 or 6 of the cover, to an apex 78. Similar walls extend from both parts 4 and 6 of the case, see Figure 2. Most partition walls 72 have a complimentary wall extending from the opposite part 4 or 6 of the case. The board is thus supported between the walls 72. In some cases, partition walls 72a extend from only one part 6 of the case.

[0011] Especially because the circuit board is multi layer, the tolerance on its thickness is significant: about 10%. This amounts to about 0.3 mm variation in thickness. It is thus not possible to clamp both partition walls up directly on the circuit board.

[0012] As may be seen from Figure 2b, peripheral walls 78 of the case are complementarily stepped in transverse cross section. A pair of opposed faces 80 and 82 extend to opposite sides of the circuit board 2 similarly to the partition walls 72. Another pair of opposed faces 84 and 86, at a different level from the faces 80 and 82, are in direct contact with each other thus acting as a dead stop.

[0013] In order to accommodate the variations in the thickness of the circuit board, a compressible conductive gasket material 77 in the form of a silicone base filled with conductive particles is deposited on the apex 78 of the partition walls and the faces 80,82 extending from the lower part 4 of the case. A suitable gasket material is available from Altocad S.A. 38 Rue des Maraichers, F75929 Paris, France under the trade name Altocad SNL 55. The material has a resistivity of 0.008 ohm cm, a hardness of 57, elongation at break 105%, adhesion on aluminium >10 N/cm<sup>2</sup>, density 2.1 g/cm<sup>3</sup> and a temperature range of -50°C to +125°C. Cure is catalysed by humidity.

[0014] In some applications the gasket material may be applied to all partition walls and both faces 80 and 82. The material is applied by a computer numerically controlled (CNC) nozzle, both the position and diameter of the nozzle being computer controlled.

[0015] The circuit board 2 is located in the part 4 of the

case by pins 84 which also locate the two halves of the case. The parts 4 and 6 of the case are held together by screws 88 extending through holes 89 in the board and through holes 90 incorporated in the partition walls 72 and in the stepped peripheral walls 79.

5

[0016] In the power amplifier shown in Figures 3 and 4, features which correspond with those of Figures 1, 2a and 2b are given corresponding reference numbers. The amplifier has a multipin connector 100 by which control data is received. Radio frequency input signals are received at a co-axial connector 102 from one output 16 or 18 of the transmit receive unit shown in Figures 1, 2a and 2b. Power output to the antenna is taken from a co-axial connector 104.

10

[0017] The circuit board 106 is multilayer, but in this example has components mounted on one side only. The other side is in direct heat conducting contact with the lower part 108 of the case. On the circuit board, the components are grouped in separate modules. An earth track surrounds each module on the board. The modules are RF isolated by partition walls 72 on the apex of which compressible conductive gasket material is deposited.

15

20

#### Claims

25

1. Electronic apparatus having modules operating at radio frequencies, said modules comprising components operatively mounted on a common circuit board contained by a conductive case which is subdivided by internal partition walls separating modules one from another, the partition walls extending from a base at an outer wall of the case to an apex adjacent the circuit board, the apex being sealed to the circuit board by a deposited compressible conductive gasket.
2. Electronic apparatus as claimed in claim 1, wherein the gasket is deposited on the apex.
3. Electronic apparatus as claimed in claim 2, wherein internal partition walls extend from opposite outer walls of the case towards opposite sides of the circuit board.
4. Electronic apparatus as claimed in any preceding claim, having peripheral walls which are stepped complementarily in transverse cross section to provide pairs of opposed surfaces at two levels, one pair of the surfaces being in direct contact with each other, the other pair extending to opposed sides of the circuit board and at least one having a compressible conductive gasket deposited thereon.

30

35

40


45

50

55

EP 0 986 293 A1

FIG. 1



EP 0 986 293 A1

FIG. 2a







FIG. 2b



EP 0 986 293 A1



EP 0 986 293 A1



EP 0 986 293 A1

European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 98 30 7227

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 5 687 470 A (HALTTUNEN MIKKO VEIJO TAPANI ET AL) 18 November 1997	1-3	H05K9/00
Y	See the whole document	4	
Y	US 5 557 507 A (KOIKE NOBORU ET AL) 17 September 1996 * column 7, line 1 - column 7, line 14; figure 3 *	4	
X	US 4 739 453 A (KUROKAWA OSAMU) 19 April 1988 * column 1, line 51 - column 1, line 60; figure 3 * * column 3, line 38 - column 3, line 45; claims 2,3 *	1-3	
X	EP 0 424 606 A (HEWLETT PACKARD CO) 2 May 1991 * claim 1; figures 3,4 *	1-3	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H05K
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 20 January 1999	Examiner Schneider, F
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (P4/C01)



## EP 0 986 293 A1

ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.

EP 98 30 7227

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20-01-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5687470 A	18-11-1997	FI 915242 A GB 2261324 A, B	07-05-1993 12-05-1993
US 5557507 A	17-09-1996	JP 7045983 A	14-02-1995
US 4739453 A	19-04-1988	CA 1284207 A	14-05-1991
EP 0424606 A	02-05-1991	US 5034856 A	23-07-1991

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82